# DATACARD® SD260™ CARD PRINTER



The SD260" card printer delivers outstanding print quality, reliability, easy operation and efficiency in a small footprint. SD Series printers outperform in their categories so you can do the same in yours. Whether you need a more secure workplace or a convenient solution for customer, student or staff identification, SD series card printers are the affordable way to print cards for many types of applications, including:

- Corporate IDs
- Healthcare IDs
- Student, visitor or staff IDs
- Retail, hospitality and loyalty cards
- Local government IDs
- Visitor IDs

## The best card issuance value on anyone's desktop

The Datacard® SD260™ one-sided card printer is packed with industry-leading innovations that make desktop ID card printing simple and economical. As part of the SD Series card printer family, the SD260 is ideal for businesses, schools, hospitals, fitness clubs and anyone who batch-issues ID cards as part of their busy workday. With competitive features and price, SD Series printers are a great value.

#### Dozens of great innovations in one great card printer family

- Superior speed and productivity. Print more cards in less time. SD Series printers are significantly faster than any other desktop card printers in their class. And TruePick™ antijam card handling accurately picks cards standard and thin with no adjustments.
- Superb image quality for high-impact IDs. TrueMatch™ printing technology an industry exclusive ensures the colors on your screen closely match the colors on your card. Batch after batch, you get consistently crisp, clean printing results from the first card to the last.
- Easy operation that anyone can master. Intuitive icons guide you through the soft-touch control panel and LCD screen. Cards and supplies are easy to load, and the ergonomically designed ribbon cartridge includes a drop-in cleaning roller.
- All the right connections for easy setup. Standard USB/Ethernet ports and the browser-based Printer Manager help you integrate SD Series printers into third-party applications as well as existing systems.



#### **DATACARD® SD260™ CARD PRINTER**

SD260 Printe	r Standard	Features	and :	Specifications
--------------	------------	----------	-------	----------------

Print technology	Direct-to-card dye-sublimation/resin thermal transfer
Print capabilities	One-sided, edge-to-edge printing; manual two-sided printing Full-color and monochrome printing Alphanumeric text, logos and digitized signatures; 1D/2D bar code images Printer pooling/sharing UV Printing Rewrite Capability
Print resolution	300 dots per inch, 256 shades per color panel High-quality mode: 300 x 600 dots per inch; enhanced text, bar code and graphics printing 300 x 1200 dots per inch; enhanced text and bar code printing
Print speed**	Full-color printing: up to 200 cards per hour, one-sided (YMCKT*); up to 155 cards per hour, two-sided (YMCKT-K*) Monochrome: up to 830 cards per hour, one-sided (black HQ*)
Card capacity	Automatic feed: 100-card input for 0.030 in. (0.76 mm) cards; 25-card output standard Manual feed: 1-card input; 5-card output for 0.030 in. (0.76 mm)
Physical dimensions	L 15.38 in. x W 6.69 in. x H 8.69 in. (39.0 cm x 17.0 cm x 22.1 cm) SD260L (long body with smart card): L 21.2 in. x W 6.9 in. x H 8.8 in. (53.9 cm x 17.5 cm x 22.4 cm) SD260S (short body with smart card): L 17.56 in. x W 6.69 in. x H 8.69 in. (44.6 cm x 17.0 cm x 22.1 cm)
Weight	8.1 lbs (3.7 kg) (depending on options) SD260L (long body with smart card): 12.0 lbs (5.4 kg) (depending on options) SD260S: 14 lbs (6.4 kg)
Connectivity	Bidirectional USB 2.0 high speed; Ethernet 10 Base-T/100-Base-TX (with activity light)
Warranties	<b>36</b> -month standard depot warranty; <b>36</b> -month printhead warranty (no pass restrictions). Full warranty details can be found in printer documentation kit.

#### **SD260 Printer Options**

Magnetic stripe encoding	Field upgradable ISO 7811 three-track option (high- and low-coercivity) JIS Type II single-track option Support for standard and custom data formats
Smart card personalization	Factory options SD260L: Single Wire DUALi Smart Card Contact/Contactless Reader/Encoder Loosely Coupled, Identive Smart Card Contact/Contactless Reader/Encoder SD260S: Loosely Coupled, Identive Smart Card Contact/Contactless Reader/Encoder Field upgradable options SD260L: Loosely Coupled, Third-party OEM Smart Card Option-Ready Hardware (for contactless reader only - encoder not included) Loosely Coupled, Third-party OEM Smart Card Option-Ready Hardware (for contact readers only encoder not included) Loosely Coupled, Identive Smart Card Contact/Contactless Reader/Encoder Loosely Coupled, pcProx Plus reader (read-only) Single Wire, DUALi Smart Card Contact/Contactless Reader/Encoder Loosely Coupled, iCLASS by HID Contactless Smart Card Encoder (read-write) SD260S: Loosely Coupled, Third-party OEM Smart Card Option-Ready Hardware (for contactless readers only - encoder not included) Loosely Coupled, Identive Smart Card Option-Ready Hardware (for contact readers only - encoder not included) Loosely Coupled, Identive Smart Card Contact/Contactless Reader/Encoder Loosely Coupled, pcProx Plus reader (read-only) Loosely Coupled, pcProx Plus reader (read-only) Loosely Coupled, iCLASS by HID Contactless Smart Card Encoder (read-write)



KL-style security lock for printer \*\*Print speeds will vary depending on ribbon type used and image being printed.

End-user upgradable Extended 200-card input hopperExtended 100-card output hopper

Note: Specifications subject to change without notice.



### **Build a complete card issuance** solution with Entrust Datacard

Datacard $^*$  SD260 $^{™}$  card printers work with Datacard® software, certified supplies and global services to give you a complete ID issuance solution that delivers exceptional results.



Phone: 1800 368 787 (1800 ENTRUSTDC) www.entrustdatacard.com australia.sales@entrustdatacard.com

South Pacific Offices: Melbourne +61 3 9535 0300 australia.sales@entrustdatacard.com | Auckland +64 9 451 9555 new.zealand.sales@entrustdatacard.com

options